



Dillon
TOYOTA LIFT

NOBLELIFT
NORTH AMERICA

LPG

FL4P50N-70N

5,000 - 7,000 lbs. Capacity

LPG Pneumatic Forklift



Capacity
5000-7000lb

High
Performance

Robust
Design

Ergonomic

Highly
Cost Effective

Easy
Maintenance

Low noise

Why choose between price and quality **WHEN YOU CAN HAVE BOTH!**



HIGHLIGHTS

- ▶ On-demand fully hydrostatic power steering (FHPS)
- ▶ 4-Way hydraulics to carriage
- ▶ Side-shift
- ▶ Intelligent buffering
- ▶ Multi-function LED Display: Speed, travel direction, fuel indicator, engine temp, oil pressure, odometer, hour meter, parking brake and more
- ▶ Spacious operator cab
- ▶ Deluxe suspension seat
- ▶ Tilt steering column
- ▶ Operator Presence System (OPS) for safe operation
- ▶ Tilt cylinder boots
- ▶ Safety Blue light
- ▶ LED rear work light, headlights, and strobe
- ▶ Rear grab bar with horn
- ▶ Easy serviceability

FL4P50N-70N 5,000 - 7,000 lbs. Capacity LPG Pneumatic Forklift

The FL4P50N-70N Series are highly efficient, durable LPG Pneumatic forklifts. They are designed to move high volumes and big loads reliably. The mast system, front/rear axles, chassis and overhead guard are engineered for the toughest conditions. Applications can include lumber yards, brick and stone distribution centers, specialized warehouses and heavy-duty manufacturing facilities. These high performance, low maintenance forklifts deliver improved productivity while ensuring operator comfort throughout the entire shift.

SIMPLE. SOLID. SMART.



RELIABILITY AND SAFETY



Heavy-duty steel chassis, axles, mast and overhead guard deliver high strength and stability for high lifting heights and heavy loads.



Radiator's plate fin heat dissipation system keeps engine running reliably, even in the most demanding applications.



Intelligent buffering effectively protects the ground and cargo from damage while forks descend to the ground.



Operator Presence System (OPS) — When operator is not in seat, the hydraulic lift and tilt controls automatically lock out and traveling is disabled.



Cast axles increase the bearing load and improve the truck structure, while prolonging vehicle service life.



Durable controller that integrates all electrical components is protected from temperature, water and vibration.



GREAT VISIBILITY. ERGONOMIC. QUIET.



Mast layout is optimized for a wide view and clear visibility while operating.



The large, ergonomic cab and user-friendly design ensures operator comfort throughout the entire work shift. Low entrance height provides operator easy and safe access.



On-Demand Fully Hydrostatic Power Steering (FHPS) guarantees smooth steering, preventing over-run and kick-back. Spinner knob allows easier one-handed steering.

GREAT VISIBILITY. ERGONOMIC. QUIET.



The angle of the steering column is easily adjusted with a lever on the left-hand side of the steering column.



Equipped with LED lamps: LED rear work lights, headlights, strobe and safety blue light. Bright light with low power consumption provides excellent visibility.



Optimized pedal position gives operator comfort throughout the entire work shift while reducing operator fatigue.



(2) USB connectors for charging and powering of additional devices during operations.



Angled exit ports direct engine air away from the operator and the cab to help operators stay cool.



Automotive-style levers for headlights and turn signals operate like a car. Easy and intuitive operating controls shorten learning time.

EASY MAINTENANCE



Gain rapid access to engine and other components with an air spring assisted engine cover and integrated hood lock. Opens wide to allow for complete access.

Automobile-style brake fluid system makes it simple to add and check the brake fluid.

Radiator cover fasteners are easily turned by hand to enable quick inspection or servicing.

Air cleaning system with tangential intake and double seal with safety filter is durable, corrosion-free, and vibration-resistant. It provides optimal filter efficiency and lower intake resistance.



Modular frame is designed based on the same chassis as the NOBLELIFT Diesel and Electric forklifts. Main components and configurations are the same. Spare parts inventory is minimized to reduce service and maintenance costs.



Hyundai L4KB Engine 60.8 HP/2,600 rpm

High Power Engine - Hyundai L4KB

High performance, durability and excellent fuel efficiency.

Type: L3

Model: L4KB

Number of cylinders: 4

Bore x Stroke: 88mm x 97mm

Displacement: 2.4L / 2359cc

Rated output: 45.4(60.8hp)/2600kw/rpm

Rated torque: 178.9/2000N.m/rpm

Powerful high-output engine provides excellent acceleration, gradeability and fast travel speed.



ENVIRONMENTALLY FRIENDLY



NOBLELIFT's LPG engines meet the tough EPA Tier IV Final and EU Stage V emission regulations for engine exhaust emissions.

NOBLELIFT has used environment friendly materials when possible — Including non-asbestos brake shoes and a new type of sealing gasket. We are committed to pursuing a clean environment.



Mast Table FL4P50N												
Designation	Lift height h3 (in)		Free lift h2 (in)		Closed mast height h1 (in)		Extended mast height h4 (in)		Tilt forward / backward a/b (°)		Capacity table (lb) C=24in without sideshift single pneumatic tires	
	FL4P50N		FL4P50N		FL4P50N		FL4P50N		FL4P50N		FL4P50N	
Two-stage ZT	79		5.3		61.8		117.1		6 / 10		5,000	
	98		5.3		71.7		136.8		6 / 10		5,000	
	118		5.3		81.5		156.5		6 / 10		5,000	
	130		5.3		87.4		168.3		6 / 10		5,000	
	138		5.3		91.3		176.1		6 / 10		5,000	
	142		5.3		93.3		180.1		6 / 10		5,000	
	146		5.3		95.3		184.0		6 / 10		5,000	
	157		5.3		103.1		195.8		6 / 6		4,900	
	169		5.3		109.1		207.6		6 / 6		4,600	
	177		5.3		113.0		215.5		6 / 6		4,300	
197		5.3		122.8		235.2		6 / 6		3,700		
Two-stage ZZ	79		24.8		61.8		116.9		6 / 10		5,000	
	98		34.7		71.7		136.5		6 / 10		5,000	
	118		44.5		81.5		156.2		6 / 10		5,000	
	130		50.4		87.4		168.0		6 / 10		5,000	
	138		54.4		91.3		175.9		6 / 10		5,000	
	142		56.3		93.3		179.8		6 / 10		5,000	
	146		58.3		95.3		183.8		6 / 6		5,000	
	157		66.2		103.1		195.6		6 / 6		4,800	
Three-stage DZ	157		41.6		78.5		196.0		6 / 6		4,700	
	171		46.5		83.5		209.8		6 / 6		4,400	
	177		48.5		85.4		215.6		6 / 6		4,100	
	189		52.4		89.6		227.4		6 / 6		3,800	
	197		58.0		95.0		235.3		6 / 6		3,400	
	217		67.2		104.2		255.0		3 / 6		2,800	
	236		76.4		113.4		274.6		3 / 6		1,900	
	256		85.6		122.6		294.3		3 / 3		1,100	
Mast Table FL4P60-70N												
Designation	Lift height h3 (in)		Free lift h2 (in)		Closed mast height h1 (in)		Extended mast height h4 (in)		Tilt forward / backward a/b (°)		Capacity table (lb) C=24in without sideshift single pneumatic tires	
	FL4P60N	FL4P70N	FL4P60N	FL4P70N	FL4P60N	FL4P70N	FL4P60N	FL4P70N	FL4P60N	FL4P70N	FL4P60N	FL4P70N
Two-stage ZT	79	79	5.5	5.5	62.0	66.1	121.2	121.2	6 / 10	6 / 10	6,000	7,000
	98	98	5.5	5.5	71.9	76.0	140.9	140.9	6 / 10	6 / 10	6,000	7,000
	118	118	5.5	5.5	81.7	85.8	160.6	160.6	6 / 10	6 / 10	6,000	7,000
	130	130	5.5	5.5	87.6	91.7	172.4	172.4	6 / 10	6 / 10	6,000	7,000
	138	138	5.5	5.5	91.5	95.7	180.3	180.3	6 / 10	6 / 10	6,000	7,000
	142	142	5.5	5.5	93.5	97.6	184.2	184.2	6 / 10	6 / 10	6,000	7,000
	146	146	5.5	5.5	95.5	99.6	188.1	188.1	6 / 10	6 / 10	6,000	7,000
	157	157	5.5	5.5	103.3	107.5	200.0	200.0	6 / 6	6 / 6	5,900	6,900
	169	169	5.5	5.5	109.3	113.4	211.8	211.8	6 / 6	6 / 6	5,700	6,500
	177	177	5.5	5.5	113.2	117.3	219.6	219.6	6 / 6	6 / 6	5,200	6,200
197	197	5.5	5.5	123.0	127.2	239.3	239.3	6 / 6	6 / 6	4,800	5,300	
Two-stage ZZ	79	79	22.2	19.3	62	66.1	121.2	121.2	6 / 10	6 / 10	6,000	7,000
	98	98	32.0	29.2	71.9	76.0	140.9	140.9	6 / 10	6 / 10	6,000	7,000
	118	118	41.9	39.0	81.7	85.8	160.6	160.6	6 / 10	6 / 10	6,000	7,000
	130	130	47.8	44.9	87.6	91.7	172.4	172.4	6 / 10	6 / 10	6,000	7,000
	138	138	51.7	48.9	91.5	95.7	180.3	180.3	6 / 10	6 / 10	6,000	7,000
	142	142	53.7	50.8	93.5	97.6	184.2	184.2	6 / 10	6 / 10	6,000	7,000
	146	146	55.6	52.8	95.5	99.6	188.1	188.1	6 / 6	6 / 6	6,000	6,800
157	157	63.5	60.7	103.3	107.5	200.0	200.0	6 / 6	6 / 6	5,900	6,700	
Three-stage DZ	157	157	38.9	36.1	78.7	78.7	200.0	200.0	6 / 6	6 / 6	5,800	6,500
	171	171	43.8	41.0	83.7	83.7	213.7	213.7	6 / 6	6 / 6	5,500	6,300
	177	177	45.8	43.0	85.6	85.6	219.6	219.6	6 / 6	6 / 6	5,200	6,000
	189	189	49.7	46.9	89.6	89.6	231.5	231.5	6 / 6	6 / 6	4,800	5,600
	197	197	55.4	52.5	95.2	95.2	239.3	239.3	6 / 6	6 / 6	4,600	5,300
	217	217	64.6	61.7	104.4	104.4	259.0	259.0	3 / 6	3 / 6	3,700	4,400
	236	236	73.7	70.9	113.6	113.6	278.7	278.7	3 / 6	3 / 6	2,800	3,100
	256	256	83.0	80.1	122.8	122.8	298.4	298.4	3 / 3	3 / 3	1,800	1,900

Identification					
1.1	Manufacturer		NOBLELIFT		
1.2	Model		FL4P50N	FL4P60N	FL4P70N
1.3	Drive (electric – battery or mains, diesel, petrol, gas, manual)		LPG		
1.4	Type of operation (hand, pedestrian, standing, seated, order picker)		Seated forklift		
1.5	Load capacity / rated load	(lb)	5,000	6,000	7,000
1.6	Load center distance	(in)	24		
1.8	Load distance, center of drive axle to fork	(in)	18.8	19.2	19.4
1.9	Wheel base	(in)	63	66.9	
Weights					
2.1	Service weight	lb	7,997	9,548	10,362
2.2	Axle loading, laden front / rear	lb	11,847 / 1,430	14,344 / 1,804	15,950 / 2,112
2.3	Axle loading, unladen front / rear	lb	3,300 / 4,697	3,850 / 5,698	3,718 / 6,644
Wheels, Chassis					
3.1	Tires (solid rubber, superelastic, pneumatic, polyurethane)		Solid pneumatic		
3.2	Tire size, front		7.00-12-12PR	28x9-15-14PR	
3.3	Tire size, rear		6.00-9-10PR	6.50-10-10PR	
3.5	Wheels, number front / rear (x = driven wheels)		2x / 2		
3.6	Track width, front	(in)	38.2	39.4	
3.7	Track width, rear	(in)	38.6		
3.8	Front tire center height from ground, laden	(in)	12.2	13.0	
3.9	Rear tire center height from ground, laden	(in)	10.4	11.0	
3.10	Front tire center height from ground, unladen	(in)	12.6	13.6	
3.11	Rear tire center height from ground, unladen	(in)	9.8	10.2	
Basic Dimensions					
4.1	Mast / fork carriage tilt forward / backward	a/b (°)	6 / 10		
4.2	Lowered mast height	(in)	79.1	81.7	84.6
4.3	Free lift	(in)	5.3		5.5
4.4	Lift height	(in)	118		
4.5	Extended mast height	(in)	161.0	164.6	164.4
4.7	Overhead load guard (cab) height	(in)	85.8	86.8	
4.8	Seat height / standing height	(in)	38.97		
4.12	Coupling height	(in)	22.8		
4.19	Overall length with forks	(in)	140.5	148.5	150.3
4.20	Length to face of forks	(in)	103.1	106.2	109.1
4.21	Overall width	(in)	45.3	47.6	
4.22	Front overhang	(in)	18.8		19.0
4.23	Rear overhang	(in)	21.4	20.9	23.9
4.24	Mast width	(in)	27.6		
4.25	Traction pin height from ground	(in)	12.0	13.0	
4.26	Fork dimensions	s/e/l (in)	1.6 / 4.8 / 42	1.8 / 4.9 / 42	2.0 / 5.1 / 42
4.27	Fork carriage width	(in)	43.3		
4.31	Ground clearance, under mast, laden / unladen	(in)	4.5 / 4.9	5.1 / 5.5	
4.32	Ground clearance, bottom of frame, laden / unladen	(in)	4.7 / 5.2	5.5 / 6.1	
4.33	Right Angle Stack with 40x48 pallet	Ast (in)	151.5	160.6	162.3
4.35	Turning radius	Wa (in)	87.8	96.5	99.2
Performance Data					
5.1	Travel speed, laden / unladen	mph	10.5 / 11.2	11.2 / 11.8	
5.2	Lift speed, laden / unladen	fpm	9.7 / 10.2	8.5 / 9.1	7.9 / 9.1
5.3	Lowering speed, laden / unladen	fpm	7.5 / 8.3	7.5 / 7.9	
5.5	Max. Drawbar pull, laden / unladen	blf	3,820 / 3,371		
5.7	Max. Gradient performance, laden / unladen	%	20 / 20		18 / 18
5.10	Service brake		Hydraulic		
5.10	Ramp parking brake	%	15		
5.10	Braking distance	in	≤236.2		
5.10	System pressure	psl	2,682		2,972